

Pryco TRIM Day Tanks have the same standard features (see below) as its Standard Day Tank counterpart, but has a smaller footprint. Trim tanks come in either a U/L Listed (Label 142) or a basic, non-U/L Listed version. The U/L Listed tanks have additional internal reinforcement, an emergency vent properly sized to the tank, and a U/L Listed label (Label 142, File #MH12807 - *Aboveground Tank for Flammable Liquids*).

### Standard features include:

- \* Removable 6½" Square Inspection Plate w/Gasket
- \* Fuel Level Gauge
- \* Heavy Duty Float Switch
- \* "Press-to-Test" Switch
- \* "Pump Running" Indicator Light
- \* Four - 1" NPT Threaded Pipe Connections
- \* One - 2" NPT Threaded Pipe Connection for Tank Vent
- \* Tank Drain (Sized To Tank Capacity)
- \* 1/3 hp thermally protected, 120vac, 1ph, 60hz, motor
- \* 2 gpm bronze gear pump w/stainless steel shafts
- \* Lift Lugs (on tanks 50 gallons and over)
- \* Removable top cover
- \* Epoxy coating inside
- \* Pryco (medium) Gray exterior paint (or an industrial color of choice)

Pryco Tanks are fabricated of heavy gauge steel by certified welders. Each tank complies with NFPA 30 and is tested to 5 psi.



Shown above is a 100-Gallon Trim Day Tank (PY100T) with a Weatherproof U/L Listed Rupture Basin.



This is a 60-Gallon Trim, Double Wall, U/L Listed, Day Tank (PY60TULDW) without its cover. With cover, it is 61" tall, 42" wide. Its depth of only 16" includes the 3" double wall area that surrounds the inner tank.



### DOUBLE WALL TANKS and RUPTURE BASINS

Please refer to sidebars on the Standard Day Tank description page (page 1).



**TRIM DAY TANKS**  
**BASIC and U/L LISTED – SINGLE and DOUBLE WALL**

SIZE IN US GAL.	SINGLE WALL		U/L LISTED SINGLE WALL			R/B <sup>(1)</sup>		DOUBLE WALL		U/L LISTED DOUBLE WALL			R/B <sup>(1)</sup>	
	MODEL	WEIGHT	MODEL	WEIGHT	VENT	WEIGHT		MODEL	WEIGHT	MODEL	WEIGHT	VENT	WEIGHT	
10	PY10T	113	PY10TUL	117	2	73		PY10TDW	220	PY10TULDW	225	2	73	
25	PY25T	137	PY25TUL	141	2	101		PY25TDW	276	PY25TULDW	281	2	114	
50	PY50T	216	PY50TUL	220	2	142		PY50TDW	440	PY50TULDW	445	2	148	
60	PY60T	224	PY60TUL	231	3	159		PY60TDW	460	PY60TULDW	469	3	164	
75	PY75T	232	PY75TUL	239	3	175		PY75TDW	479	PY75TULDW	488	3	184	
100	PY100T	248	PY100TUL	255	3	194		PY100TDW	517	PY100TULDW	526	3	212	

NOTE#1 - Add R/B (Rupture Basin) Weight to Tank Weight to determine total weight.